

F-03WT

SPEAKER SYSTEM



F-03WT is a full-range surface-mount speaker system designed to deliver high-quality audio for a variety of applications. This versatility makes it ideal for foreground or background music playback, as well as public address announcements. The F-03T boasts a sleek aesthetic that seamlessly integrates with walls and ceilings. Hardware incorporates a temporary hanging feature, allowing for easy and secure single-handed installation with effortless wiring and angle adjustments.

Key features

- Versatile 3.5-inch full-range surface-mount speaker system
- Perfect for music and announcements
- Sleek design for seamless integration with walls and ceilings
- Safe and easy installations with included mounting bracket
- Temporary docking feature allows effortless wiring and positioning
- Flexible angle adjustment for both wall and ceiling mounts
- Ideal for permanent installs or portable setups


Specifications

Enclosure	Bass-reflex type
Rated Input	15 W (100 V line, 70 V line)
Power Handling	Rated noise power: 30 W (8 Ω) Continuous program: 60 W (8 Ω)
Rated Impedance	8 Ω 100 V line: 670 Ω (15 W), 2 k Ω (5 W), 3.3 k Ω (3 W), 10 k Ω (1 W) 70 V line: 330 Ω (15 W), 670 Ω (7.5 W), 2 k Ω (2.5 W), 3.3 k Ω (1.5 W), 10 k Ω (0.5 W)
Sensitivity	87 dB (1 W, 1 m) at installation in 1/2 free sound field
Frequency Response	85 Hz - 20 kHz, -10 dB at installation in 1/2 free sound field
Directivity Angle	Horizontal: 100°, Vertical: 100°
Speaker Component	9 cm (3.5") Full-range, PP cone-type
Input Terminal	Push-in Terminal
Installation Environment	Indoor installation
Operating Temperature	-10 °C to +50 °C (14 °F to 122 °F)
Finish	Enclosure: HIPS, white (RAL 9016 equivalent), paint Grille: Aluminum, white (RAL 9016 equivalent), paint Speaker bracket: Die-cast aluminum, white (RAL 9016 equivalent), paint Base bracket: Steel plate, t4, white (RAL 9016 equivalent), paint Base bracket cover: HIPS, white (RAL 9016 equivalent)
Dimensions	130 (W) x 221 (H) x 132 (D) mm (5.12" x 8.7" x 5.2")
Weight	1.7 kg (3.75 lb)
Included Accessories	Speaker bracket x 1, Base bracket x 1, Base bracket cover x 1, Bracket fixing screw x 1 set
Optional Accessories	Adapter plate: HY-F03W Speaker stand: ST-34B Note: K&M 19780 or K&M 19610 is required.

(*1) Rated noise power is defined by IEC60268-5. Continuous program is 3 dB above Rated noise power.

Note: Bolts and nuts for mounting the bracket to the wall or ceiling are not included. Prepare them separately.


Dimensions




UNIT:mm

Dimensions

■ Wall mounting example




The angle can be adjusted in 15° steps.




Vertical installation	Horizontal installation
A 170 (6.69") or more	220 (8.66") or more
B 250 (9.84") or more	250 (9.84") or more


Dimensions of wall mounting hole
(base bracket (accessory))



■ Ceiling mounting example




The angle can be adjusted in 15° steps.



Vertical installation	Horizontal installation
A 150 (5.91") or more	150 (5.91") or more
B 250 (9.84") or more	250 (9.84") or more

Dimensions of wall or ceiling mount hole
(base bracket (accessory))



The angle can be adjusted up to 40° left or right from the "Reference point" in the Base bracket.

A&E specifications

The speaker shall be a full-range bass-reflex type enclosure suitable for ceiling or wall mounting. The low-frequency driver shall be a 9 cm (3.5") PP cone-type full-range speaker. The speaker shall have a rated noise power handling capacity of 30 W (8 Ω) and a continuous program power capacity of 60 W (8 Ω). The rated input for the speaker shall be 15 W when connected to 100 V or 70 V line systems. The speaker shall offer multiple tap settings, including 670 Ω (15 W), 2 k Ω (5 W), 3.3 k Ω (3 W), and 10 k Ω (1 W) for the 100 V line, and 330 Ω (15 W), 670 Ω (7.5 W), 2 k Ω (2.5 W), 3.3 k Ω (1.5 W), and 10 k Ω (0.5 W) for the 70 V line. The impedance shall be 8 Ω for direct connection. The speaker shall have a sensitivity of 87 dB at 1 W, measured at 1 m distance in a 1/2 free sound field. The frequency response of the speaker shall range from 85 Hz to 20 kHz, with a -10 dB variance in a 1/2 free sound field. The directivity angle of the speaker shall be 100° horizontally and 100° vertically, ensuring broad coverage for optimal sound dispersion. The enclosure shall be constructed of high-impact polystyrene (HIPS) and finished in either black or white. The grille shall be made of aluminum and finished to match the enclosure color. The mounting bracket and base bracket shall be made of die-cast aluminum and steel plate respectively, both painted to match the enclosure finish. The base bracket should be capable of supporting the mounting bracket that is attached to the enclosure and let it stay without fixing the nut as temporally hanging. The speaker shall be equipped with push-in terminal for input connection. The speaker shall be designed for indoor installation and be capable of operating in a temperature range from -10°C to +50°C (14°F to 122°F). The overall dimensions of the speaker shall be 130 mm (W) x 221 mm (H) x 132 mm (D) (5.12" x 8.7" x 5.2"), and the weight shall be 1.7 kg (3.75 lbs.). Included accessories shall consist of one speaker bracket, one base bracket, one base bracket cover, and one set of bracket fixing screws. Optional extras:

Adapter Plate: HY-F03B/ HY-F03W

Speaker Stand: ST-34B with compatibility for K&M 19780 or K&M 19610 stands

manufactured by TOA Corporation. Manufacturer: TOA Corporation

Model: F-03BT/ F-03WT