

IP-101RM

IP Remote Microphone with 7 Inch LCD



IP-101RM is an IP network remote control microphone, equipped with power input connector, USB connector, audio input and output connector, RJ45 network connector, and so on. IP network remote control microphone is not only used in IP PA paging communication, but also can initiate emergency broadcast and realize two-way talk with other devices.

Key features

- Network touchscreen control
- Trigger paging, message playback
- Monitoring function
- Intercom function with other IP-101RM

Specifications

Power Source	DC 24V / 1A
Display	7.0 inch touch screen, resolution 800 x 480 pixels
Current Consumption	≤20W
Audio Input	1 Vrms, unbalance, 10kΩ
Audio Output	Unbalance, output power 10mW, 32Ω
Frequency Response	20Hz - 16kHz
Signal to Noise Ratio	Above 90dB
Monitor Speaker	8Ω/3W
Network I/F	10BASE-T/100BASE-TX, auto-negotiation
Network Protocol	ARP, UDP, TCP/IP, ICMP, IGMP, SIP
Operating Temperature	0°C - 40°C
Operating Humidity	Less than 90% RH (no condensation)
Dimensions	254(W) x 32.5(H) x 134(D) mm
Included Accessories	Adapter(DC24V/1A) x1, Terminal (3.5 - 5P) x1, Microphone Pole (IM-320) x1